Gebhardt-Stahl GmbH
Runtestraße 33 59457 Werl
Postfach 80 35 59079 Werl
Tel. +49 2922 9733-0
Fax +49 2922 9733-290
info@gebhardt-stahl.de
www.gebhardt-stahl.de

PRODUCT DATASHEET – 308180010

Stand: 20.03.2024

Article number:	308180010 – GRD 18-8 308200010 – GRD 18-10 308210010 – GRD 18-12 308210011 – GRD 18-14 308210015 – GRD 18-16 308220010 - GRD 21-14+15 308230010 - GRD 21-16+18 308240010 - GRD 21-20+22 308250010 - GRD 21-25+28 308260010 - GRD 21-31+35 308260020 – GRD 32-28 308270010 – GRD 32-31 308280010 – GRD 32-35 308280110 – GRD 32-40 308280120 – GRD 32-45 308280130 - GRD 32-50 308290010 - GRD 43-40 308300010 - GRD 43-45 308310010 - GRD 43-50 308320010 - GRD 43-56 308330010 - GRD 43-63 308340010 - GRD 43-71 308350010 - GRD 43-80 308360010 - GRD 43-90 308370010 - GRD 54-56 308380010 - GRD 54-63 308390010 - GRD 54-71 308400010 - GRD 54-80 308410010 - GRD 54-90 308420010 - GRD 54-100 308430010 - GRD 54-112 308440010 - GRD 54-125 308450010 - GRD 54-140 308460010 - GRD 54-160
Product name:	Access doors for spiral tubes, galvanized, with polyethylene foam gasket
Field of application:	Access door for round and oval ductwork. Provides easy access to ductwork for cleaning and inspection.
Material:	Upper and lower shell: galvanized steel
Dimensions:	GRD 18: Width: 180 mm x 80 mm GRD 21: Width: 200 mm x 100 mm GRD 32: Width: 300 mm x 200 mm GRD 43: Width: 400 mm x 300 mm GRD 54: Width: 500 mm x 400 mm
Hand knobs:	Polyamide; star-shaped With embedded metal thread Colour: red
Seal:	Polyethylene foam gasket Colour: white Temperature resistance: -30 °C to +80 °C Grease resistance: good Resistance to condensation water: good Free from halogen

The intention of this product leaflet is to provide non-binding information and should only be interpreted as such. The information takes the current state of technical developments and developments in the chemical industry. We reserve the right to make modifications relating to the product as well as to develop it further. No liability on our part can be derived from this. Users should check the suitability of the product for the intended purpose by conducting their own tests

Gebhardt-Stahl GmbH
Runtestraße 33 59457 Werl
Postfach 80 35 59079 Werl
Tel. +49 2922 9733-0
Fax +49 2922 9733-290
info@gebhardt-stahl.de
www.gebhardt-stahl.de

Screw and nut:	Carriage bolt DIN 603, galvanized steel Hex nut ISO 4035, galvanized steel
Weight:	GRD18: 0,32 kg/pc. GRD21: 0,38 kg/pc. GRD32: 1,05 kg/pc. GRD43: 2,28 kg/pc. GRD54: 4,20 kg/pc.
PU:	GRD18: Boxes à 50 pcs. GRD21: Boxes à 50 pcs. GRD32: Boxes à 25 pcs. GRD43: Boxes à 10 pcs. GRD54: Boxes à 6 pcs.
Remarks:	Tested to DIN EN 1507 Class D (TÜV-Nord certified) Self-adhesive drilling plate in each bag Fixed by two star-shaped hand knobs with embedded metal thread

The intention of this product leaflet is to provide non-binding information and should only be interpreted as such. The information takes the current state of technical developments and developments in the chemical industry. We reserve the right to make modifications relating to the product as well as to develop it further. No liability on our part can be derived from this. Users should check the suitability of the product for the intended purpose by conducting their own tests