

PRODUCT DATA SHEET – 310XX0000
As of: 23.05.2019

Article number:	310100000 – 9 x 4 mm 310110000 – 12 x 4 mm 310070000 – 15 x 4 mm 310160000 – 20 x 4 mm 310170000 – 25 x 4 mm 310015000 – 9 x 6 mm 310060000 – 15 x 6 mm			
Product name:	Sealing tape			
Material:	Polyethylene foam			
Colour:	Grey			
Adhesive:	Synthetic rubber hot-melt			
Liner:	No liner			
Peel adhesion:	DIN EN 1939 material break			
Temperature range:	- 30°C to + 80°C			
Resistance to high humidity:	Very good			
Density:	ISO 845 ~ 30 kg/m³			
Tensile strength::	ISO 1926	lengthwise	325 kPa	
		crosswise	220 kPa	
Elongation at break:	ISO 1926	lengthwise	125 %	
		crosswise	115 %	

The intention of this product leaflet is to provide non-binding information and should only be interpreted as such. The information takes the current state of technical developments and developments in the chemical industry. We reserve the right to make modifications relating to the product as well as to develop it further. No liability on our part can be derived from this. Users should check the suitability of the product for the intended purpose by conducting their own tests.

Compressive strength at 50 % compression:	ISO 844	98 kPa
Compression set 25 % / 22 h at 23°C:	ISO 1856-B	20 % (0,5 h after discharge) 12 % (24 h after discharge)
Water absorption (7 d):	< 1 Vol.-%	
Certificates/Tests:	Tested to DIN EN ISO 846 (suitable for use in ventilation systems according to VDI 6022)	
Remarks:	• Free of paint-wetting impairment substances (PWIS- / LABS-free) • Silicone-free • Halogen-free • Lead-free • Cadmium-free • Chrome 6-free	