

Spiral Tube

| Nominal Diameter mm | Standard Gauge mm | Standard Length mm | Weight Kg/m |
|---------------------|-------------------|--------------------|-------------|
| 100 | 0.5 | 3000 | 1.42 |
| 125 | 0.5 | 3000 | 1.78 |
| 150 | 0.5 | 3000 | 2.13 |
| 160 | 0.5 | 3000 | 2.28 |
| 180 | 0.5 | 3000 | 3.07 |
| 200 | 0.5 | 3000 | 3.41 |
| 224 | 0.5 | 3000 | 3.82 |
| 250 | 0.5 | 3000 | 4.26 |
| 300 | 0.5 | 3000 | 5.12 |
| 315 | 0.5 | 3000 | 5.38 |
| 355 | 0.6 | 3000 | 8.08 |
| 400 | 0.6 | 3000 | 9.10 |
| 450 | 0.6 | 3000 | 10.23 |
| 500 | 0.8 | 3000 | 11.37 |
| 560 | 0.8 | 3000 | 12.73 |
| 600 | 0.8 | 3000 | 13.65 |
| 630 | 0.8 | 3000 | 14.33 |
| 710 | 0.8 | 3000 | 16.15 |
| 800 | 0.8 | 3000 | 18.20 |
| 900 | 1.0 | 3000 | 25.58 |
| 1000 | 1.0 | 3000 | 28.43 |
| 1120 | 1.0 | 3000 | 38.21 |
| 1250 | 1.0 | 3000 | 42.64 |

Description

Spirally Wound Tube

- Comes in a wide variety of diameters.
- Manufactured in standard 3m lengths.
- Custom lengths can be made upon request.
- Galvanised material

Circular Fittings

McCaig Collim stock a complete range of circular fittings.